



G-TEK® POLYKOR™ BLENDED SHELL WITH POLYURETHANE COATED SMOOTH GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor™ blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, excellent puncture resistance and outstanding wet/dry grip
- Knit Wrist helps prevent dirt and debris from entering the glove
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).



TECHNICAL DATA

MATERIAL	PolyKor™ Fiber / Polyurethane					
CONSTRUCTION	Seamless knit					
COLOR	Shell: ■ Salt & Pepper / Coating: ■ Gray					
WRIST STYLE	Continuous knit					
SIZES	6 -11					
PACKAGING	1 pair per bag, 12 pairs per dozen, 72 pairs per case					
CASE DIMENSIONS	16.7" x 11.2" x 11.2" / 42.5cm x 28.5cm x 28.5cm					
CASE WEIGHT	6	7	8	9	10	11
	7.7 lbs 3.5 kgs	7.9 lbs 3.6 kgss	8.4 lbs 3.8 kgs	8.8 lbs 4 kgs	9.5 lbs 4.3 kgs	9.9 lbs 4.5 kgs
COO	China					

DIMENSIONS (IN/CM)

	6	7	8	9	10	11
A	7.5 / 19	8.3 / 21	9.1 / 23	9.4 / 24	9.8 / 25	10 / 25.3
B	3.3 / 8.5	3.5 / 9	3.7 / 9.3	3.9 / 10	4.1 / 10.3	4.2 / 10.5
C	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

PERFORMANCE PROPERTIES

EN388: 4342	ASTM F2992-15 ANSI Cut Level A2 (Adopted by ANSI/ISEA 02/16)					
ABRASION	0	1	2	3	4	-
CUT (2003)	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

