

TECHNICAL SHEET

G-TEK® POLYKOR™ BLENDED GLOVE WITH DOUBLE-DIPPED NITRILE COATED MICRO-SURFACE GRIP



- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Double-dipped nitrile micro-surface coating helps extend the life of the glove and provide excellent abrasion resistance
- Knit wrist helps prevent dirt and debris from entering the glove
- · Cotton color binding denotes sizing
- · Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Electronics
- · Glass cutting
- · Sheet metal handling
- General duty
- Parts assembly
- · Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	PolyKor™ Shell with Nitrile Micro-Surface Coating						
CONSTRUCTION	Seamless knit						
COLOR	Shell: ■ Hi-Vis orange / Coating: ■ Black						
WRIST STYLE	Continuous knit						
SIZES	7 -11						
PACKAGING	1 pair per bag, 12 pairs per dozen, 72 pairs per case						
CASE DIMENSIONS	14.2" x 11.8" x 12.6" / 36cm x 30cm x 32cm						
CASE WEIGHT	7	8	9	10	11		
	11.7 lbs	12.3 lbs	13.5 lbs	14 lbs	15 lbs		
	5.4 kgs	5.6 kgs	6.1 kgs	6.4 kgs	6.9 kgs		
C00	China						

PERFORMANCE PROPERTIES

EN388: 4544	ASTM F2992-15 ANSI Cut Level A3 (Adopted by ANSI/ISEA 02/16)						
ABRASION	0	1	2	3	4	-	
CUT (2003)	0	1	2	3	4	5	
TEAR	0	1	2	3	4	-	
PUNCTURE	0	1	2	3	4	-	







DIMENSIONS (IN/CM)

	7				11
Α	9.3 / 23.7	9.7 / 24.7	10.1 / 25.7	10.5 / 26.6	10.7 / 27.2
В	3.6 / 9.2	3.9 / 9.9	4.1 / 10.4	4.2 / 10.6	4.4 / 11.2
Н	Red	Yellow	■ Brown	■ Black	Blue

